
Contents

Streszczenie	ix
Summary	xi
1 Introduction	1
1.1 Approaches to mobility management	4
1.2 Mobility in the Internet	5
1.3 Research on IP mobility management	5
1.4 Contribution	7
1.5 Organization of the text	10
2 Architecture restrictions to support host mobility	13
2.1 Topology control in communications systems	13
2.1.1 Identities, name spaces and names	14
2.1.2 Name lookup and name resolution	15
2.1.3 Path computation	16
2.1.4 Naming schemes	17
2.1.5 Routing in the ‘small world’ networks	20
2.1.6 Alternative approaches – compact routing	22
2.2 Internet architecture	23
2.2.1 Principles	24
2.2.2 Communication model	26
2.2.3 Address allocation schemes	29
2.3 Internet architecture restrictions to suport mobility	31

3 Requirements for mobility management system	37
3.1 Architecture options to support mobility	38
3.2 Handover management strategies	39
3.2.1 Mobility management in the network layer	40
3.2.2 Mobility management in the data-link layer	41
3.2.3 Mobility management above the network layer	42
3.3 Handover initiation and execution control	42
3.4 Functional requirements	43
3.5 Technical requirements	45
3.6 Design considerations	47
3.6.1 Host and endpoint identification	47
3.6.2 Binding management	47
3.6.3 Binding security	48
3.6.4 Routing scalability	49
3.6.5 Protocol interworking	49
3.6.6 Cross-layer improvements	50
3.6.7 Transport layer problem	51
3.6.8 Movement anticipation and detection	52
3.6.9 Systems interworking	54
3.6.10 Application limitations	55
3.6.11 Handover scope	55
3.6.12 Technology heterogeneity	56
3.6.13 Handover timing	57
3.7 Factors in system design process	57
3.8 Specification guidelines	59
4 Mobility management in 2G and 3G cellular systems	61
4.1 Mobility management in GSM	62
4.1.1 System architecture	62
4.1.2 GPRS packet data service	64
4.1.3 GPRS system architecture	65
4.1.4 Mobility management	70
4.1.5 Location management in standby mode	73
4.2 Mobility management in UMTS	74
4.2.1 System architecture	74
4.2.2 Location management in GSM and UMTS	78
4.2.3 Handover types	82
4.2.4 Intra-RNS soft handover	84
4.2.5 Inter-RNS soft handover	86
4.2.6 Handover with SRNS relocation	88

4.2.7	IPv6 address autoconfiguration	90
4.2.8	IPv6 address autoconfiguration in UMTS	91
4.2.9	Radio resource control in mobility management	92
4.2.10	Handover with FMIPv6 control	92
5	Mobility management in the Internet	97
5.1	Models for mobility management	99
5.2	Schemes for global mobility management	101
5.2.1	Host mobility with Mobile IPv4 protocol	101
5.2.2	Host mobility with Mobile IPv6 protocol	106
5.2.3	Comparative analysis of MIPv4 and MIPv6	110
5.2.4	Fast handovers in Mobile IPv6 protocol	112
5.2.5	Host mobility with Hierarchical MIPv6 protocol . .	116
5.3	Schemes for local mobility management	118
5.3.1	Host mobility with Proxy MIPv6 protocol	121
5.3.2	Fast Handovers for Proxy Mobile IPv6	126
5.4	Discussion	128
6	Security management in all-IP system	133
6.1	Session model	135
6.2	Handover control model	136
6.3	Security model	137
6.3.1	Administrative domain model	138
6.3.2	Trust model	139
6.3.3	Trust groups, trust levels and trust domains . . .	141
6.3.4	Federations	142
6.3.5	Federations impact	144
6.3.6	Secure group key management	145
6.4	Discussion	147
7	Mobility management in LTE Evolved Packet System	151
7.1	Mobility management system – an overview	152
7.2	Architectures for 3GPP access systems	156
7.3	Architectures for non-3GPP access systems	157
7.3.1	Non-roaming architecture for non-3GPP systems .	158
7.3.2	Roaming architecture for non-3GPP systems . . .	159
7.4	Handover in the Evolved Packet System	163
7.5	Emerging models and schemes	165
7.5.1	Local offloading and mobility	165
7.5.2	Distributed mobility management	166

7.5.3	Host identity protocol	167
7.5.4	Locator-identifier separation	167
8	Summary	169
	Bibliography	179